

A. PSA Strips

These pressure-sensitive strips are made of aluminum oxide, glue-bonded on a cloth backing. Just press them onto a flat surface such as a wood stick. Strips measure 1" x 11".

Grit	Item#	Box of 100	Grit	Item#	Box of 100
80	107-2550		240	107-2250	
120	107-2050		320	107-2300	
180	107-2150		400	107-2350	



A

B-F PSA Discs

These flexible discs are made of aluminum oxide resin-bonded on a cloth backing for greater durability. Pressure-sensitive adhesive backing withstands the high frictional heat generated when a disc is in use. PSA Discs will stay on until removed from the holder by hand. Each disc has a peel-off backing to ensure adhesive freshness.

Dia.	Grit	Item#	Box of 100
B. 1/2"	80	105-0508	
	120	105-0512	
	180	105-0518	
	240	105-0524	
	320	105-0532	
C. 3/4"	80	105-0708	
	120	105-0712	
	180	105-0718	
	240	105-0724	
	320	105-0732	
D. 1"	60	105-1006	
	80	105-1008	
	120	105-1012	
	180	105-1018	
	240	105-1024	
	320	105-1032	
E. 1 1/2"	80	105-1508	
	120	105-1512	
	180	105-1518	
	240	105-1524	
	320	105-1532	
F. 2"	60	105-2006	
	80	105-2008	
	120	105-2012	
	180	105-2018	
	240	105-2024	
	320	105-2032	
	400	105-2040	



B



C



D



E



F

G-K PSA Disc Holders – 1/8" and 1/4" Shanks

Flexible rubber pads mounted on shanks to hold any PSA (Pressure Sensitive Adhesive) Discs. Rubber pads also provide cushioning for uniform finish. Actual pad diameters are slightly smaller than specified to ensure easy removal of discs and to prevent material from marring the work surface. Max. Operating speed: 22,000 rpm.

Head Dia.	1/8" Shank Item#	1/4" Shank Item#	EACH Prices*	
G. 1/2"	840-0010	840-0020	1-2	3+
H. 3/4"	840-0030	840-0040		
I. 1"	840-0050	840-0060		
J. 1 1/2"	840-0070	840-0080		
K. 2"	—	840-0090		

*Quantity discount for orders of one item number only; not assorted.



G

H

I

J



K

L. Paper Discs, Aluminum Oxide

Paper discs are coated with Aluminum Oxide abrasive on one side. All have 1/16" arbor hole. See pp. 584-585 for mandrel selection.

Grit	Dia.	Item#	PKG of 100	
80	1 1/2"	845-1006	1-9	10+
150	1 1/2"	845-1007		
220	1 1/2"	845-1008		



L