



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Page 1 of 13

Printing date 02/02/2015

Reviewed on 02/02/2015

## 1 Identification

- **Product identifier**
- **Trade name:** Super Lube
- **Article number:** DAC 113
- **Application of the substance / the mixture** Lubricant
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
DAC Industries, Inc.  
1636 Gervais Avenue Suite 9  
Maplewood, MN 55109  
Phone: (651) 748-1750
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



Flam. Aerosol 1 H222 Extremely flammable aerosol.



Press. Gas H280 Contains gas under pressure; may explode if heated.



Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS04 GHS05 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

Zinc Dialkyldithiophosphate

2,2'-iminodiethanol

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing mist, vapors, or spray.

P280 Wear protective gloves and eye protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

· **Hazard description:**

· **WHMIS-symbols:**

A - Compressed gas

B5 - Flammable aerosol

D2B - Toxic material causing other toxic effects



· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 2)

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

68476-86-8	Petroleum gases, liquefied, (Nota K, -R45, R46, <0.1% 1,3-butadiene buta-1,3-diene)	50-100%
	Flam. Gas 1, H220 Press. Gas, H280	
68649-42-3	Zinc Dialkyldithiophosphate	2.5-10%
	Eye Dam. 1, H318 Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Sulfonate Blend (proprietary)	2.5-10%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
68603-42-9	Coconut diethanolamide	≤ 2.5%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
111-42-2	2,2'-iminoethanol	≤ 2.5%
	Carc. 2, H351; STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	

- Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

### 4 First-aid measures

- Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

- After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

In cases of frostbite, rinse with plenty of water. Do not remove clothing.

- After eye contact:

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 3)

- **After swallowing:**  
Unlikely route of exposure.  
Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
Headache  
Breathing difficulty  
Coughing  
Dizziness  
Frostbite  
Allergic reactions  
Nausea in case of ingestion.  
Gastric or intestinal disorders when ingested.  
Disorientation
- **Danger**  
Danger of impaired breathing.  
Danger of pulmonary edema.  
Danger of pneumonia.
- **Indication of any immediate medical attention and special treatment needed**  
Contains Zinc Dialkyldithiophosphate. May produce an allergic reaction.  
Medical supervision for at least 48 hours.  
Later observation for pneumonia and pulmonary edema.  
If necessary oxygen respiration treatment.  
Treat skin and mucous membrane with antihistamine and corticoid preparations.  
Treat frost-bitten areas appropriately.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
Alcohol resistant foam  
Fire-extinguishing powder  
Gaseous extinguishing agents  
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
Danger of receptacles bursting because of high vapor pressure if heated.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information**  
Eliminate all ignition sources if safe to do so.  
Cool endangered receptacles with water fog.

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

(Contd. of page 4)

### 6 Accidental release measures

**· Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Protect from heat.

**· Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

**· Methods and material for containment and cleaning up:**

Allow to evaporate.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

**· Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Emergency cooling must be available in case of nearby fire.

Keep respiratory protective device available.

**· Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

Observe official regulations on storing packagings with pressurized containers.

Avoid storage near extreme heat, ignition sources or open flame.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 5)

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Further information about storage conditions:**

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

Storage Temperatures : <122 ° F / <50 ° C.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**111-42-2 2,2'-iminodiethanol**

REL (USA)	Long-term value: 15 mg/m <sup>3</sup> , 3 ppm
-----------	---

TLV (USA)	Long-term value: 1* mg/m <sup>3</sup> , 0.2* ppm
-----------	--

	Skin; *inhalable fraction and vapor
--	-------------------------------------

EL (Canada)	Long-term value: 2 mg/m <sup>3</sup>
-------------	--------------------------------------

	Skin, IARC 2B
--	---------------

EV (Canada)	Long-term value: 2 mg/m <sup>3</sup>
-------------	--------------------------------------

LMPE (Mexico)	Long-term value: 2 mg/m <sup>3</sup>
---------------	--------------------------------------

	A3, PIEL
--	----------

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Engineering controls:** No further relevant information available.

· **Breathing equipment:**

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

### Trade name: Super Lube

(Contd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Neoprene gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment** Avoid release to the environment.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Color:

Clear

· **Odor:**

Light

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

· **Boiling point/Boiling range:** Not applicable, as aerosol.

· **Flash point:**

-104 °C (-155 °F) (PMCC)

· **Flammability (solid, gaseous):**

Not applicable.

· **Auto-ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not self-igniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

Not determined.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

		(Contd. of page 7)
<b>Upper:</b>	Not determined.	
· <b>Vapor pressure:</b>	Not determined.	
· <b>Density at 20 °C (68 °F):</b>	<1.0 g/cm³ (<8.345 lbs/gal)	
· <b>Relative density</b>	Not determined.	
· <b>Vapour density</b>	Not determined.	
· <b>Evaporation rate</b>	Not applicable.	
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.	
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.	
· <b>Viscosity:</b>		
<b>Dynamic:</b>	Not determined.	
<b>Kinematic:</b>	Not determined.	
· <b>Other information</b>	No further relevant information available.	

**10 Stability and reactivity**

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.
- **Possibility of hazardous reactions**  
Extremely flammable aerosol.  
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.  
Develops readily flammable gases / fumes.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.  
Danger of receptacles bursting because of high vapor pressure if heated.  
Toxic fumes may be released if heated above the decomposition point.  
Reacts with acids.  
Reacts with alkali (yes).  
Reacts with oxidizing agents.
- **Conditions to avoid**  
Avoid acids.  
Keep ignition sources away - Do not smoke.  
Store away from oxidizing agents.  
Keep away from heat and direct sunlight.
- **Incompatible materials:** Oxidizers, strong bases, strong acids
- **Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)  
Sulfur oxides (SOx)  
Hydrocarbons  
Toxic metal oxide smoke

(Contd. on page 9)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 8)

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** May cause irritation, rash, hypersensitivity.
- **on the eye:** Irritating effect.
- **Sensitization:**  
Sensitization possible through skin contact.  
Sensitizing effect through inhalation is possible with prolonged exposure.
- **Additional toxicological information:**  
Irritant  
Danger through skin absorption.  
May cause cancer.  
Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
Toxic and/or corrosive effects may be delayed up to 24 hours.  
Contains Zinc Dialkyldithiophosphate. May produce an allergic reaction.
- **Carcinogenic categories**
- **NTP (National Toxicology Program)**  
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**  
None of the ingredients is listed.
- **Probable Routes of Exposure**  
Inhalation.  
Eye contact.  
Skin contact.
- **Acute effects (acute toxicity, irritation and corrosivity):** May cause an allergic skin reaction.
- **Repeated Dose Toxicity:**  
Repeated exposures may result in skin and/or respiratory sensitivity.  
May cause damage to organs through prolonged or repeated exposure.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **Persistence and degradability** The product is biodegradable after prolonged adaptation.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**  
Harmful to fish  
Due to mechanical actions of the product (e.g. agglutinations) damages may occur.  
The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 9)

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

UN1950

· **DOT, ADR, IMDG, IATA**

Aerosols, flammable  
1950 AEROSOLS, flammable

· **UN proper shipping name**

AEROSOLS, flammable

· **DOT**



· **ADR**

1950 AEROSOLS, flammable

· **IMDG, IATA**

AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**

2.1

· **Class**

2.1

· **Label**

· **ADR**



· **Class**

2 5F Gases

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 10)

· <b>Label</b>	2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1
· <b>Label</b>	2.1
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	Not Regulated
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Gases
· <b>Danger code (Kemler):</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	UN1950, Aerosols, 2.1

## 15 Regulatory information

· <b>Safety, health and environmental regulations/legislation specific for the substance or mixture</b>
· <b>SARA</b>
· <b>Section 355 (extremely hazardous substances):</b>
None of the ingredients is listed.
· <b>Section 313 (Specific toxic chemical listings):</b>
111-42-2   2,2'-iminodiethanol
· <b>TSCA (Toxic Substances Control Act):</b>
All ingredients are listed.
· <b>Proposition 65 (California)</b>
· <b>Chemicals known to cause cancer:</b>
68603-42-9   Coconut diethanolamide
111-42-2   2,2'-iminodiethanol
· <b>Chemicals known to cause reproductive toxicity for females:</b>
None of the ingredients are listed.
· <b>Chemicals known to cause reproductive toxicity for males:</b>
None of the ingredients is listed.
· <b>Chemicals known to cause developmental toxicity:</b>
None of the ingredients is listed.
· <b>Carcinogenic categories</b>
· <b>EPA (Environmental Protection Agency)</b>
None of the ingredients is listed.

(Contd. on page 12)

# Safety Data Sheet

## acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 11)

· **IARC (International Agency for Research on Cancer)**

111-42-2	2,2'-iminodiethanol	3
----------	---------------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

111-42-2	2,2'-iminodiethanol	A3
----------	---------------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **State Right to Know Listings**

None of the ingredients is listed.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

111-42-2	2,2'-iminodiethanol
----------	---------------------

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 02/02/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

(Contd. on page 13)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/02/2015

Reviewed on 02/02/2015

**Trade name: Super Lube**

(Contd. of page 12)

**Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)