

Center Inserts




- Sits flush within body assembly
- Designed for efficient installation and removal
- Stainless steel construction
- Provides excellent traceability

This center insert has a stainless steel construction and is always at the same level as the body of the date stamp. Diameters ranging 4 mm to 20 mm are available. Center Inserts are easily changed reducing downtime.

| SPECIFICATIONS | |
|-----------------|--------------|
| Hardness | 48 - 54 Rc |
| Material Type | INOX. 1.4034 |
| Unit of Measure | Metric DIN |


CH Series

Compact Height




RF Series

Remains Flush



CUMSA Series

PCS Standard



| CATALOG NO. | A mm | B mm |
|-------------|------|------|
| DCP04-AO | 2.2 | 8 |
| DCP04- | 2.2 | 8 |
| DCP05-AO | 3.1 | 8 |
| DCP05- | 3.1 | 8 |
| DCP06-AO | 3.1 | 8 |
| DCP06- | 3.1 | 8 |
| DCP08-AO | 4.4 | 10 |
| DCP08- | 4.4 | 10 |
| DCP10-AO | 5.2 | 12 |
| DCP10- | 5.2 | 12 |
| DCP12-AO | 6.2 | 14 |
| DCP12- | 6.2 | 14 |
| DCP16-AO | 8.2 | 14 |
| DCP16- | 8.2 | 14 |
| DCP20-AO | 11 | 16 |
| DCP20- | 11 | 16 |

| CATALOG NO. | A mm | B mm |
|-------------|------|------|
| DFP03-AO | 1.6 | 9 |
| DFP03- | 1.6 | 9 |
| DFP04-AO | 2.5 | 10.5 |
| DFP04- | 2.5 | 10.5 |
| DFP05-AO | 3.1 | 13 |
| DFP05- | 3.1 | 13 |
| DFP06-AO | 3.1 | 13 |
| DFP06- | 3.1 | 13 |
| DFP08-AO | 4.6 | 14 |
| DFP08- | 4.6 | 14 |
| DFP10-AO | 4.6 | 14 |
| DFP10- | 4.6 | 14 |
| DFP12-AO | 6.4 | 17 |
| DFP12- | 6.4 | 17 |
| DFP16-AO | 8.4 | 23 |
| DFP16- | 8.4 | 23 |

| CATALOG NO. | A mm | B mm |
|-------------|------|------|
| DP 2275 | 2.2 | 7.5 |
| DP 2275- | 2.2 | 7.5 |
| DP 3075 | 3.0 | 7.5 |
| DP 3075- | 3.0 | 7.5 |
| DP 3217 | 3.2 | 17 |
| DP 3217- | 3.2 | 17 |
| DP 4717 | 4.7 | 17 |
| DP 4717- | 4.7 | 17 |
| DP 5717 | 5.7 | 17 |
| DP 5717- | 5.7 | 17 |
| DP 6717 | 6.7 | 17 |
| DP 6717- | 6.7 | 17 |
| DP 8717 | 8.7 | 17 |
| DP 8717- | 8.7 | 17 |
| DP 10717 | 10.7 | 17 |
| DP 10717- | 10.7 | 17 |

Note: When ordering add the two digit year to the end of the catalog number (i.e. DCP04-18)

AO = Arrow Only